Kybernetika

Krishnan Balachandran; D. Somasundaram Controllability of a class of nonlinear systems with distributed delays in control

Kybernetika, Vol. 19 (1983), No. 6, 475--482

Persistent URL: http://dml.cz/dmlcz/124706

Terms of use:

© Institute of Information Theory and Automation AS CR, 1983

Institute of Mathematics of the Academy of Sciences of the Czech Republic provides access to digitized documents strictly for personal use. Each copy of any part of this document must contain these *Terms of use*.



This paper has been digitized, optimized for electronic delivery and stamped with digital signature within the project *DML-CZ*: The Czech Digital Mathematics Library http://project.dml.cz

CONTROLLABILITY OF A CLASS OF NONLINEAR SYSTEMS WITH DISTRIBUTED DELAYS IN CONTROL

K. BALACHANDRAN, D. SOMASUNDARAM

Sufficient conditions for global relative controllability of a class of nonlinear time varying systems with distributed delays in the control and implicit derivative are given. The results are obtained by using the measure of noncompactness of a set and the Darbo fixed point theorem.

1. INTRODUCTION

In the study of economic, biological and physiological systems as well as electromagnetic systems composed of subsystems interconnected by hydraulic, mechanical and various other linkages, one encounters phenomena which cannot be readily modelled unless relations involving time delays are admitted. Examples of such models have been given in [8], which also includes the systems considered here. In particular, models for systems with delay in the control occur in the study of gaspressurized bipropellant rocket systems, in population models and in some complex economic systems [3]. More specifically, models for systems with distributed delays in the control occur in the study of agricultural economics [2] and in population dynamics [1]. We shall consider the nonlinear systems which are perturbations of linear systems.

Using the measure of noncompactness of a set and Darbo's fixed point theorem, controllability of nonlinear systems with implicit derivative has been studied by Dacka [4]. In [5] Dacka has extended the method to other types of nonlinear systems with delays in control and implicit derivative. Controllability of nonlinear systems with distributed delays in control has been considered by Klamka [6, 7], with the aid of Schauder's fixed point theorem. In this paper we shall examine the controllability of nonlinear systems with distributed delays in control and implicit derivative by the method of Dacka.

2. MATHEMATICAL PRELIMINARIES

Let $(X, \|\cdot\|)$ be a Banach space and E a bounded subset of X. In this paper the following definition of the measure of noncompactness of a set E is used [4, 9]

$$\mu(E) = \inf\{r > 0; E \text{ can be covered by a finite number of balls}$$

whose radii are smaller than r .

The following version of Darbo's fixed point theorem being a generalisation of Schauder's fixed point theorem shows the usefulness of the measure of noncompactness. "If S is a nonempty bounded closed convex subset of X and $P: S \to S$ is a continuous mapping such that for any set $E \subset S$ we have

$$\mu(PE) \le k \ \mu(E)$$

where k is a constant $0 \le k < 1$, then P has a fixed point".

For the space of continuous functions $C_n[t_0, t_1]$ the measure of noncompactness of a set E is given by

(2)
$$\mu(E) = \frac{1}{2} w_0(E) = \frac{1}{2} \lim_{h \to 0^+} w(E, h)$$

where w(E, h) is the common modulus of continuity of the functions which belong to the set E, that is

(3)
$$w(E, h) = \sup_{x \in E} [\sup |x(t) - x(s)| : |t - s| \le h]$$

where as in the space of differentiable functions $C_n^1[t_0, t_1]$ we have

(4)
$$\mu(E) = \frac{1}{2} w_0(DE)$$

where

$$DE = \{\dot{x} : x \in E\}$$

If the space X is the Cartesian product $X=X_1\times X_2$ of two spaces X_1 and X_2 , then for any set $E\subset X$

$$\mu(E) = \max \left[\mu(E_1), \mu(E_2) \right]$$

where E_1 and E_2 denote the natural projections of E onto X_1 and X_2 respectively. Let h>0 be a given real number. For functions $u:[t_0-h,t_1]\to\mathbb{R}^m$ and $t\in[t_0,t_1]$, let u_t denote the function on [-h,0) defined by $u_t(s)=u(t+s)$ for $s\in[-h,0)$. Furthermore if the function g(s) is of bounded variation on [-h,0], then the symbol $\operatorname{Var} g(s)$ will denote the variation of the function g(s) on the interval [-h,0]. The integrals are in the Lebesque-Stieltjes sense [6].

3. STATEMENT OF THE PROBLEM

Let us consider the nonlinear time varying system with distributed delays in the control represented by the following differential equation

(5)
$$\dot{x}(t) = A(t) x(t) + \int_{-b}^{0} d_{s} B(t, s) u(t + s) + f(t, x, \dot{x}, u)$$

satisfied everywhere on the interval $[t_0, t_1]$, and where $x(t) \in \mathbb{R}^n$, u(t) is an m-dimensional control vector and $u \in C_m[t_0 - h, t_1]$, A(t) is the $n \times n$ matrix whose elements are continuous in t and $f(t, x, \dot{x}, u)$ is an n-dimensional continuous function in its arguments. The matrix B(t, s) is an $n \times m$ dimensional, continuous in t for fixed s and is of bounded variation in s on [-h, 0] for each $t \in [t_0, t_1]$ and continuous from left in s on the interval (-h, 0). The symbol d_s in (5) denotes that the integral is in the Lebesque-Stieltjes sense. Assume that

(6)
$$||A(t)|| \le M, \quad ||B(t,s)|| \le N \quad \text{for each} \quad s \in [-h,0]$$
$$|f(t,x,y,u)| \le K \quad \text{for} \quad t \in [t_0,t_1] \quad \text{and} \quad x,y \in \mathbb{R}^n, \quad u \in \mathbb{R}^m$$

where M, N and K are positive constants. Further for every $y, \ \bar{y} \in \mathbb{R}^n$ and $x \in \mathbb{R}^n$, $u \in \mathbb{R}^m$, $t \in [t_0, t_1]$

(7)
$$|f(t, x, y, u) - f(t, x, \bar{y}, u)| \le k|y - \bar{y}|$$

where k is a positive constant such that $0 \le k < 1$. The following definition of the complete state of the system and global relative controllability are assumed [6].

Definition 1. The set $z(t) = \{x(t), u_t\}$ is said to be the complete state of the system (5) at time t.

Definition 2. The system (5) is globally relatively controllable on $[t_0, t_1]$ if for every complete state $z(t_0)$ and every $x_1 \in \mathbb{R}^n$ there exist a control u(t) defined on $[t_0, t_1]$ such that the corresponding trajectory of the system (5) satisfies the condition $x(t_1) = x_1$.

The solution of the system (5) is given by

(8)
$$x(t) = F(t, t_0) x(t_0) + \int_{t_0}^t F(t, \tau) \left(\int_{-h}^0 d_s B(\tau, s) u(\tau + s) \right) d\tau + \int_{-h}^t F(t, \tau) f(\tau, x, \dot{x}, u) d\tau$$

where $F(t, t_0)$ is the transition matrix of the system $\dot{x}(t) = A(t) x(t)$ with $F(t_0, t_0) = I$. The second term in the right hand side of (8) contains the values of u(t) for $t < t_0$ as well as for $t > t_0$. The values of the control u(t) for $t \in [t_0 - h, t_0)$ enter into the definition of the initial complete state $z(t_0)$. This can be separated by changing the order of integration and using the unsymmetric Fubini theorem, we have the following equalities [6, 7]

$$x(t) = F(t, t_0) x(t_0) + \int_{t_0}^{t} F(t, \tau) f(\tau, x, \dot{x}, u) d\tau +$$

$$+ \int_{-h}^{0} d_{Bs} \left(\int_{t_0}^{t} (F(t, \tau) B(\tau, s) u(\tau + s) d\tau) \right) =$$

$$= F(t, t_0) x(t_0) + \int_{t_0}^{t} F(t, \tau) f(\tau, x, \dot{x}, u) d\tau +$$

$$+ \int_{-h}^{0} d_{Bs} \left(\int_{t_0 + s}^{t_0} F(t, \tau - s) B(\tau - s, s) u_{t_0} d\tau \right) +$$

$$+ \int_{-h}^{0} d_{Bs} \left(\int_{t_0}^{t_0 + s} F(t, \tau - s) B(\tau - s, s) u(\tau) d\tau \right)$$

where d_{Bs} denotes that the integration is in the Lebesque-Stieltjes sense with respect to the variable s in the function B(t, s).

Let us introduce the following notation.

(10)
$$B_{t}(\tau, s) = \begin{cases} B(\tau, s) & \text{for } \tau \leq t \\ 0 & \text{for } \tau > t \end{cases}$$

Hence x(t) can be expressed in the following form

(11)
$$x(t) = F(t, t_0) x(t_0) + \int_{t_0}^t F(t, \tau) f(\tau, x, \dot{x}, u) d\tau + \int_{-h}^0 d_{Bs} \left(\int_{t_0+s}^{t_0} F(t, \tau - s) B(\tau - s, s) u_{t_0} d\tau \right) + \int_{-h}^0 d_{Bs} \left(\int_{t_0}^t F(t, \tau - s) B_t(\tau - s, s) u(\tau) d\tau \right)$$

Using again unsymmetric Fubini's theorem, the equality (11) can be rewritten as follows

(12)
$$x(t) = F(t, t_0) x(t_0) + \int_{t_0}^{t} F(t, \tau) f(\tau, x, \dot{x}, u) d\tau + \int_{-h}^{0} d_{Bs} \left(\int_{t_0 + s}^{t_0} F(t, \tau - s) B(\tau - s, s) u_{t_0} d\tau \right) + \int_{t_0}^{t} \left(\int_{-h}^{0} F(t, \tau - s) d_s B_t(\tau - s, s) \right) u(\tau) d\tau$$

Now let us consider the solution x(t) of system (5) for $t = t_1$

(13)
$$x(t_1) = F(t_1, t_0) x(t_0) + \int_{t_0}^{t_1} F(t_1, \tau) f(\tau, x, \dot{x}, u) d\tau +$$

$$+ \int_{-h}^{0} d_{Bs} \left(\int_{t_0 + s}^{t_0} F(t_1, \tau - s) B(\tau - s, s) u_{t_0} d\tau \right) +$$

$$+ \int_{t_0}^{t_1} \left(\int_{-h}^{0} F(t_1, \tau - s) d_s B_{t_1}(\tau - s, s) \right) u(\tau) d\tau$$

For brevity let us introduce the following notations

(14)
$$S(t_1, \tau) = \int_{-\infty}^{\infty} F(t_1, \tau - s) \, \mathrm{d}_s \, B_{t_1}(\tau - s, s)$$

and

(15)
$$q(z(t_0), x(t_1)) = x_1 - F(t_1, t_0) x(t_0) - \int_{t_0}^{t_1} F(t_1, \tau) f(\tau, x, \dot{x}, u) d\tau - \int_{-h}^{0} d_{Bs} \left(\int_{t_0 + s}^{t_0} F(t_1, \tau - s) B(\tau - s, s) u_{t_0} d\tau \right)$$

Define the controllability matrix $W(t_0, t_1)$ by

(16)
$$W(t_0, t_1) = \int_{t_0}^{t_1} S(t_1, \tau) S'(t_1, \tau) d\tau$$

where the prime indicates the matrix transpose.

Remark. It should be noted that under the assumption that the function f satisfies the Lipschitz condition with respect to the state variables, the response is uniquely determined by any control.

4. MAIN RESULT

Theorem. Given the system (5) with conditions (6) and (7). Assume that the matrix $W(t_0, t_1)$ is non-singular for $t_1 > t_0$. Then the system is globally relatively controllable on $[t_0, t_1]$.

Proof. The proof of the theorem is similar to the proof given in [4] and hence it will be only sketched. Let us consider the Banach space.

$$B[t_0, t_1] = C_m[t_0, t_1] \times C_n^1[t_0, t_1].$$

Define the following nonlinear mapping of the space B.

$$T(\lceil u, x \rceil)(t) = \lceil T_1(\lceil u, x \rceil)(t), T_2(\lceil u, x \rceil)(t) \rceil$$

where the pair of operators T_1 and T_2 is defined as follows

(17)
$$T_{1}(\llbracket u,x\rrbracket)(t) = S'(t_{1},t) W^{-1}(t_{0},t_{1}) q(z(t_{0}),x_{1})$$
 and
$$T_{2}(\llbracket u,x\rrbracket)(t) = F(t,t_{0}) x(t_{0}) + \int_{t_{0}}^{t} F(t,\tau) f(\tau,x,x,T_{1}(\llbracket u,x\rrbracket)) d\tau + \int_{-h}^{0} d_{Bs} \left(\int_{t_{0}+s}^{t_{0}} F(t,\tau-s) B(\tau-s,s) u_{t_{0}} d\tau \right) + \int_{-h}^{t} S(t,\tau) T_{1}(\llbracket u,x\rrbracket)(\tau) d\tau$$

(here $z(t_0)$ and x_1 are chosen arbitrarily). It is easy to see that the operator T is continuous, since all the functions involved in the definition of T are continuous and it transforms the space $B[t_0, t_1]$ into itself.

Consider the closed convex subset of B

(19)
$$H = \{ [u, x] : ||u|| \le N_1, ||x|| \le N_2, ||Dx|| \le N_3 \}$$

since the Lebesque-Stieltjes integral is finite, the positive constants $N_1,\,N_2$ and N_3 are defined by

$$+ (t_1 - t_0) K \exp(2M(t_1 - t_0)) + K_1]$$
(21)
$$N_2 = \exp(M(t_1 - t_0)) |x(t_0)| + K(t_1 - t_0) \exp(M(t_1 - t_0)) + K_1 + (t_1 - t_0) K_2 N_1$$
(22)
$$N_3 = MN_2 + NN_1 K_3 + K$$

 $N_1 = K_2 \|W^{-1}(t_0, t_1)\| \|x_1\| + \exp(M(t_1 - t_0)) |x(t_0)| +$

$$\begin{split} K_1 &= \left\| \int_{-h}^{0} \mathrm{d}_{Bs} \left(\int_{t_0 + s}^{t_0} F(t_1, \tau - s) \, B(\tau - s, s) \, u_{t_0} \, \mathrm{d}\tau \right) \right\| \\ K_2 &= \max_{t_0 \leq \tau \leq t_1} \left\| S(t_1, \tau) \right\|, \quad K_3 &= \max_{t_0 \leq t \leq t_1} \operatorname{Var}_{s \in [-h, 0)} B(t, s) \end{split}$$

The set H is bounded, closed and convex in B. The operator T transform H into H. It is easily seen that for each pair $[u, x] \in H$ we have

(23)
$$w(T_1[u, x]), h) \leq w(S', h) a$$

where

(20)

$$a = \sup_{[u,x] \in H} \{ \| W^{-1}(t_0,t_1) \| \ q(z(t_0),x_1) \}$$

Since the function S does not depend on the choice of the points in H, all the functions $T_1([u,x)]$ (t) have a uniformly bounded modulus of continuity, hence, they are equicontinuous.

All the functions $T_2([u, x])(t)$ are also equicontinuous, since they have uniformly bounded derivatives. Now we shall find an estimate of the modulus of continuity of the functions $DT_2([u, x])(t)$.

$$\begin{aligned} \left| DT_{2}(\llbracket u, x \rrbracket)(t) - DT_{2}(\llbracket u, x \rrbracket)(\tilde{t}) \right| &\leq \left| A(t) \ T_{2}(\llbracket u, x \rrbracket)(t) - A(\tilde{t}) \ T_{2}(\llbracket u, x \rrbracket)(\tilde{t}) \right| + \\ (24) + \left| \int_{-h}^{0} d_{s} \ B(t, s) \ T_{1}(\llbracket u, x \rrbracket)(t + s) - \int_{-h}^{0} d_{s} \ B(\tilde{t}, s) \ T_{1}(\llbracket u, x \rrbracket)(\tilde{t} + s) \right| + \\ + \left| f(t, x(t), \dot{x}(t), T_{1}(\llbracket u, x \rrbracket)(t)) - f(\tilde{t}, x(\tilde{t}), \dot{x}(\tilde{t}), T_{1}(\llbracket u, x \rrbracket)(\tilde{t})) \right| \end{aligned}$$

For the first two terms of the right hand side of inequality (24) we may give the upper estimate as $\beta_0(|t-\bar{t}|)$, where β_0 is a non-negative function such that $\lim_{h\to 0^+} \beta_0(h) = 0$ and that it may be chosen independently of the choice of the element $\bar{l}_{u}(x) = H$. In the same manner we find that the last term on the right of (24) can be estimated from above by $k|\dot{x}(t) - \dot{x}(\bar{t})| + \beta_1(|t-\bar{t}|)$. Letting $\beta = \beta_0 + \beta_1$ we finally obtain

(25)
$$w(DT_2(\lceil u, x \rceil), h) \leq kw(Dx, h) + \beta(h)$$

Hence by (2) and (3) we conclude that for any set $E \subset H$

$$w_0(T_1E) = 0$$
 and $w_0(T_2E) \le kw_0(DE_2)$

where E_2 is the natural projection of the set E on the space $C_n^1[t_0,t_1]$. Hence, it follows that

$$\mu(TE) \leq k \mu(E)$$
.

By the Darbo fixed point theorem the mapping T has at least one fixed point, therefore there exists functions $u^* \in C_m[t_0, t_1]$ and $x^* \in C_n[t_0, t_1]$ such that

(26)
$$u^*(t) = T_1([u^*, x^*])(t)$$

(27)
$$x^*(t) = T_2([u^*, x^*])(t)$$

Substituting this fixed point into (17) and (18), a direct differentiation of (18) with respect to t shows that $x^*(t)$ is a solution to the system (5) for the control $u^*(t)$. It is easy to verify that the control $u^*(t)$ steer the system (5) from the complete initial state $z(t_0)$ to $x_1 \in \mathbb{R}^n$, on the interval $[t_0, t_1]$ and since $z(t_0)$ and x_1 have been chosen arbitrarily, then by Definition 2, system (5) is globally relatively controllable on $[t_0, t_1]$.

5. CONCLUSION

Using the measure of noncompactness of a set and Darbo's fixed point theorem sufficient conditions fot global relative controllability of nonlinear systems with distributed delays in control and implicit derivative have been derived.

(Received August 19, 1982.)

REFERENCES

- Z. Artstein: Linear systems with delayed controls A reduction. IEEE Trans. Automat. Control AC-27 (1982), 4, 869—879.
- [2] Z. Artstein and G. Tadmor: Linear systems with indirect controls The underlying measures. SIAM J. Control Optim. 20 (1982), 1, 96—111.
- [3] H. T. Banks and M. Q. Jacobs: The optimization of trajectories of linear functional differential equations. SIAM J. Control δ (1970), 4, 461–488.
- [4] C. Dacka: On the controllability of a class of nonlinear systems. IEEE Trans. Automat. Control AC-25 (1980), 2, 263-266.
- [5] C. Dacka: Relative controllability of perturbed nonlinear systems with delay in control. IEEE Trans. Automat. Control AC-27 (1982), 1, 268-270.
- [6] J. Klamka: Relative controllability of nonlinear systems with distributed delays in control. Internat. J. Control 28 (1978), 2, 307-312.
- [7] J. Klamka: Controllability of nonlinear systems with distributed delay in control. Internat. J. Control 31 (1980), 5, 811—819.
- [8] A. Manitius: Mathematical Models of Hereditary Systems. Research Report CRM-462, Centre de Recherches Mathematiques, Université de Montreal, Montreal 1974.
- [9] B. J. Sadovskii: Limit compact and condensing operators (in Russian). Uspehi Mat. Nauk
 27 (1972), 1, 81-146, (English translation) Russian Mathematical Surveys 27 (1972), 1,
 85-156.
 - K. Balachandran, D. Somasundaram, Department of Mathematics, Bharathiar University, Coimbatore 641 046, Tamil Nadu. India.